



### **Architect Specifications:**

<u>Description:</u>	Super Duty SportFloor Rolled/Tiled Rubber--made from recycled crumb rubber.
<u>Weight</u>	3/8" 2.1 lbs sq/ft, 1/2" 2.5 lbs. sq/ft.
<u>Colors:</u>	20% {standard} Color Fleck single color or in combination. Sixteen colors available.
<u>Design:</u>	Continuous rolls of rubber flooring.
<u>Sizes:</u>	48" X 50' standard roll sizes.
<u>Packed:</u>	Palletized.
<u>Flammability:</u>	Meets federal regulation #DOC FF1-70.
<u>Installation:</u>	Full spread with HRB1000 Adhesive.
<u>Maintenance:</u>	Hose down (outdoor), damp mop and let dry (indoor).
<u>Leadtime:</u>	Variable, depending on quantity, but almost always less than 7 days.

### **Specific Technical Data**

Density:	ASTM D3676	68.3lb.s/cubic foot
Hardness:	ASTM D2240	Shore A65 +/- 5
Slip Resistance:	ASTM D C1028	Friction Coefficient .084-.090
Abrasion:	ASTM D4060	2,000 cycles taber abraser 1kg, .329-.35g loss
Flammability:	ATSM E648	Critical Radiant Flux <0.10 W/cm <sup>2</sup>
Acoustics:	Excellent	
Chemicals:	Resistant to most acids and chlorine	
VOC's:	No measurable units	

