

# PRODUCT SPECIFICATIONS

Classic Rubber



## DESCRIPTION

- Hero Classic Rubber is a collection of premium, competitive rubber flooring products, which includes rolls and tiles.

## EPDM CONTENT

- 10% - 90% Color Fleck Single Color

## DESIGN

- Continuous Rolls of Rubber Flooring and Tiles, which include Square, Interlocking, Eco-Lock and Mega

## PACKAGING

- Wrapped Rolls, Palletized

## DIMENSIONS:

THICKNESS	POUNDS/ SQ FT.	ROLL LENGTH	SQ FT./ROLL
3mm (1/8")	0.80	75'	300 sq ft
4mm (5/32")	0.95	75'	300 sq ft
6mm (1/4")	1.60	75'	300 sq ft
8mm (5/16")	1.90	50'	200 sq ft
9mm (3/8")	2.20	50'	200 sq ft
12mm (1/2")	2.60	50'	200 sq ft
18mm (3/4")	4.40	15'	60 sq ft

## TECHNICAL INFORMATION:

SPECS	STANDARD	RATING FOR ROLLS AND TILES*
Density	D3676	68.3lbs/cubic foot
Tensile Strength	ASTM D412	265 psi
Tear Resistance	ASTM D413	Average Elongation at break 1.52
Hardness	D2240	Shore A 65 ± 5
Slip Resistance	D C1028	Friction Coefficient .084 - .090
Abrasion	D4060	2,000 cycles taber abraser 1kg, 0.329g - 0.35g loss
Flammability	ASTM E648	Critical Radiant Flux <0.10W/cm <sup>2</sup>
Chemicals	N/A	Resistant to most acids and chlorine
Volatile Organic Compounds	CDPH v1.2	< .05mg/m <sup>3</sup>

\*Rolls are 3mm, 4mm, 6mm, 8mm, 9mm, and 12mm. Eco-Lock Tiles are 6mm and 8mm. Square and Interlocking Tiles are 6mm, 8mm, 9mm, and 12mm