



SPECS	HERO VALUES
Plank Width	7" / 178mm
Plank Length	48" / 1219mm
Overall Thickness	2.5mm
System	Glue Down/LLT
Edge Profile	Micro-Beveled
Wear Layer	22mil/.56mm
Planks/Carton	18 Glue Down/10 LLT
Sq Ft/Carton	41.98 Glue Down/23.23 LLT
Product Weight	37.48lbs/ct GD - 34.92lbs/ct LLT
Cartons/Pallet	55
Electrostatic Propensity of Carpets	Max Avg: 1.3kv Negative
Critical Radiant Flux	Class 1
Smoke Density	Passes < 450
Flexibility of Resilient Flooring Materials	Passes 6.0mm Mandrel
Dimensional Stability of Resilient Flooring after Exposure to Heat	0.002 inch per 12" length 0.006 per 12" width
Thickness of Resilient Flooring Materials Having Flat Surfaces	0.102"
Short Term Indentation & Residual Indentation of Resilient Flooring	0.008"
Dynamic Coefficient of Friction of Hard Surface Floors	DCOF 0.46
Static Load Limit 3,000 PSI	0.012"
Static Load Limit 2,000 PSI	0.008"
Static Load Limit 1,000 PSI	0.003"
Resistance to Chemicals of Resilient Flooring	Chemical & Stain Resistance Superior Performance
Heavy Metal Content Analysis	Clear