



COLORS



Arctic



Fennec



Gray



Swift

SIZES



12"x24"



24"x48"

MOSAICS & TRIM PIECES

2"x2" on 12"x12" Sheet Mosaic

2"x6" on 12"x12" Brick Mosaic

4"x24" Bullnose

6"x12" Cove Base

SURFACES

Matte

Polished

COLOR VARIATIONS

V2

TECHNICAL INFORMATION

SPECS	TEST	HERO VALUES
WATER ABSORPTION	C373	$\leq 0.1\%$
THICKNESS DIMENSION	C499	$\leq \pm 0.04$ Inc.
FACIAL DIMENSION	C499	$\leq \pm 0.25\%$
WARPAGE AVERAGE DIAGONAL	C485	$\leq \pm 0.40\%$
WARPAGE AVERAGE EDGE	C485	$\leq \pm 0.40\%$
WEDGING AVERAGE	C502	$\leq \pm 0.25\%$
BOND STRENGTH	C482	≥ 200 psi
BREAKING STRENGTH	C648	≥ 400 lbf
HARDNESS (MOHS)	Scratch Test (Not Regulated)	≥ 7
VISIBLE ABRASION RESISTANCE FOR GLAZE TILES	C1027	Class 4
FROST RESISTANCE	C1026	No evidence of damage
CHEMICAL RESISTANCE	C650	Class A
STAIN RESISTANCE	C1378	Class A*
DCOF	DCOF Acutest (wet)	$\geq 0.52^*$

*All values given are for matte or honed material. No values are given for polished material. Hero Flooring does not recommend polished surfaces in area subject to exposure from grease, oil, or water.