

FEATURES


RECYCLED RUBBER FROM ATHLETIC SHOES

ZERO TIRES, ZERO TIRE ODOR


APPROVED FOR AREAS WITH FREE WEIGHTS WHEN USING 8MM THICKNESS OR GREATER

30% NIKE GRIND

COLORS




Space Jam




Home Game




MVP




Teamwork




Bengals




Ducks




Eagles




Hornets



Broncos



Road Trip




Cleveland

TECHNICAL INFORMATION

SPECS	TEST	HERO VALUES
DENSITY	ASTM D3676	68.3lbs/cubic foot
HARDNESS	ASTM D2240	Shore A65 +/- 5
SLIP RESISTANCE	ASTM C1028	Friction Coefficient .084 - .090
ABRASION	ASTM D4060	2,000 cycles taber abraser 1kg, .329-.35g loss
FLAMMABILITY	ASTM E648 Critical Radiant Flux	.31 Watts/cm ²
ACOUSTICS		Excellent
CHEMICALS		Resistant to most acids and chlorine
VOC'S		No measurable units

SIZES

48"x25' Roll
48"x50' Roll
24"x24" Square/Interlocking
24"x36" Square
38"x38" Square/Interlocking
48"x72" Square/Interlocking



THICKNESS

4-19mm Square, 6-19mm Interlocking, 6-12mm Roll

CERTIFICATION

Declare.

