

FEATURES

RECYCLED RUBBER FROM ATHLETIC SHOES

ZERO TIRES, ZERO TIRE ODOR


APPROVED FOR AREAS WITH FREE WEIGHTS WHEN USING 8MM THICKNESS OR GREATER

30% NIKE GRIND


COLORS



Play




Balance




Hustle




Dream




Ignite




Spark




Shine




Grow




Swim



Focus



Elevate



Build

HERO
RUBBER

MADE WITH



NIKE GRIND

TECHNICAL INFORMATION

SPECS	TEST	HERO VALUES
DENSITY	ASTM D3676	68.3lbs/cubic foot
HARDNESS	ASTM D2240	Shore A65 +/- 5
SLIP RESISTANCE	ASTM C1028	Friction Coefficient .084 - .090
ABRASION	ASTM D4060	2,000 cycles taber abraser 1kg, .329-.35g loss
ACOUSTICS		Excellent
CHEMICALS		Resistant to most acids and chlorine
VOC'S		No measurable units

STANDARD SIZES

48"x25' Roll


48"x50' Roll

24"x24" Straight Edge/Interlocking

48"x72" Straight Edge/Interlocking

24"x24"

48"x72"



48"x25' Roll
48"x50' Roll

THICKNESS

4-19mm Square, 6-19mm Interlocking, 6-12mm Roll

CERTIFICATION

Declare.

